

Premium

Heat & Oil Protective Glove

HN50



Article No.	HN50
Coating Material	Neoprene
Coating Color	Black
Liner	Double Lined Jersey
Liner Color	White
Finishing	Crinkle
Cuff Style	Gauntlet
Gauge	N/A
Size	8,10
Style in Length	18" (available in 26")

PERFORMANCE

- Neoprene coating providing superb heat resistance up to 350 D (Degrees C.)
- Excellent resistance to oils(in particular to **hot oil**), chemicals and greases
- Crinkled finish offering excellent grip in both dry and wet working conditions
- Double lined jersey contributing great warmth working under -20 D (Degrees C.)
- Unique coating formulation contributing extra flexibility and reducing hand fatigue

APPLICATION

- Barbecue
- Baking and roasting
- Iron and Steel manufacturing
- Circuit board manufacturing
- Objects handling in hot/cold of environments contact with chemicals and oils

www.fortessafety.com

info@fortessafety.com




Tel. +86 2157832572

Fax. +86 2157832892

Version 2018

FORTES

CERTIFICATION

 EN388 2222X	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	 ISO 13997 A B C D E F
	TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4	
 EN407 43XX4X	BURNING BEHAVIOUR 0 1 2 3 4	CONTACT HEAT 0 1 2 3 4	
	CONVECTIVE HEAT 0 1 2 3 4	RADIANT HEAT 0 1 2 3 4	
	SMALL SPLASHES OF MOLTEN METAL 0 1 2 3 4	LARGE SPLASHES OF MOLTEN METAL 0 1 2 3 4	

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Size Available	(8) Medium	(10) X Large
Palm Width	10.50	12.00
Length	45.00	

PACKING

Bag	Pair pack
Carton	30 bags per carton

GLOVE CARE

Laundering	Rinse the gloves in running water before removing, using a neutral detergent if necessary
Storage	Store the glove in their original packing protected from sources of ozone or ignition

RECOMMENDATION FOR USE

Do not use against open flames or temperatures < - 50 °C or > 400°C

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2018

FORTES