Reinforced Crotch 18gg Cut Glove with Sandy Nitrile





Article No.	BN9SX
Coating Material	Nitrile
Coating Color	Black
Liner	UHMWPE/Glass
Liner Color	Salt/Pepper
Finishing	Sandy
Cuff Style	Knit wrist
Gauge	18
Size	5,6,7,8,9,10,11,12
Reinforcement	Nitrile

PERFORMANCE

- Reinforcement (between thumb and index fingers) greatly extends glove life to save your cost and provides extra protection in the most weak area
- 18 gauge exclusive lining technology contributing it as a thinnest & finest cut C glove in the market
- Over 33% lighter than a standard cut C nitrile glove
- Perfect dexterity, flexibility & fitting
- 360° breathability to keep your hands cool at work
- Sanitized® hygiene function offers increased freshness, comfort and protection

APPLICATION

- Automotive industry
- Glass industry
- Paper industry
- Blades manufacturing
- Machinery and equipment maintenance

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021



CERTIFICATION

EN388

4X43C

ABRASION **CUTTING**

01234 012345

PUNCTURE TEARING

0 1 2 3 4 01234

CUT

ANSI

OEKO-TEX® STANDARD 100

CONTACT HEAT

RADIANT HEAT

LARGE SPLASHES OF MOLTEN METAL

01234

01234



ISO 13997

ABCDEF

FLAMMABILITY EN407

01234

CONVECTIVE HEAT

01234

SMALL SPLASHES OF MOLTEN METAL X1XXXX

01234

01234

For more information, please visit here

DIMENSIONS (+/- 0.50 cm)

Sizes	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
Available	2X Small	X Small	Small	Medium	Large	X Large	2X Large	3X Large
Palm Width	8.00	8.50	9.00	9.50	10.00	10.50	11.00	11.50
Length	21.00	22.00	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs per carton

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

It is cut resistant glove not cut proof, do not use them next to moving machinery.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

