

Heat Protection 10gg Cut Glove with Crinkle Latex

KL5Y



Article No.	KL5Y
Coating Material	Latex
Coating Color	Blue
Liner	Aramid /Steel fiber
Liner Color	Yellow
Finishing	Crinkle
Cuff Style	Knit wrist
Gauge	10
Size	5,6,7,8,9,10,11,12

PERFORMANCE

- ISO 13997 TDM cut level E and ANSI cut A5 approved
- Perfect combination of cut and puncture protection along with excellent grip
- Super grip in both dry and wet working conditions
- 360° breathability to keep your hands cool at work
- Sanitized® hygiene function offers increased freshness, comfort and protection
- Excellent heat protection

APPLICATION

- Automotive industry
- Glass industry
- Paper industry
- Blades manufacturing
- Machinery and equipment maintenance

www.fortessafety.com

info@fortessafety.com






Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES

CERTIFICATION

	EN388	ABRASION	0 1 2 3 4	CUTTING	0 1 2 3 4 5		ANSI		
3X43E		TEARING	0 1 2 3 4	PUNCTURE	0 1 2 3 4	A5			
		ISO 13997	A B C D E F			CUT			
	EN407	FLAMMABILITY	0 1 2 3 4					CONTACT HEAT	0 1 2 3 4
		CONVECTIVE HEAT	0 1 2 3 4					RADIANT HEAT	0 1 2 3 4
X2XXXX		SMALL SPLASHES OF MOLTEN METAL	0 1 2 3 4					LARGE SPLASHES OF MOLTEN METAL	0 1 2 3 4

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
	2X Small	X Small	Small	Medium	Large	X Large	2X Large	3X Large
Palm Width	8.00	8.50	9.00	9.50	10.00	10.50	11.00	11.50
Length	21.00	22.00	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

It is cut resistant glove not cut proof, do not use them next to moving machinery.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES