

Heat Protection Cut Glove with Leather Palm

LN5G



Article No.	LN5G
Coating Material	Nitrile
Coating Color	Black
Liner	UHMWPE/Steel
Liner Color	Grey
Finishing	Foamed
Cuff Style	Knit wrist
Gauge	13
Size	7,8,9,10,11,12

PERFORMANCE

- ISO 13997 TDM cut level F and ANSI cut A8 approved
- Super heat and puncture protection
- Excellent resistance to oils and acids in both dry and wet environments
- Advanced yarns technology contributes to high cut protection but still soft, flexible and comfortable
- Considerable leather design in the palm to provide excellent heat resistance, extra protection but still remains great grip

APPLICATION

- Automobile
- Glass industry
- Construction
- Handling of ceramics, metal sheets, plastic injection moulds etc.

www.fortessafety.com

info@fortessafety.com







Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES

CERTIFICATION

EN388  4X44F	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	ANSI  A8 CUT			
	TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4				
	ISO 13997 A B C D E F					
EN407  X2XXXX	FLAMMABILITY 0 1 2 3 4	CONTACT HEAT 0 1 2 3 4				
	CONVECTIVE HEAT 0 1 2 3 4	RADIANT HEAT 0 1 2 3 4				
	SMALL SPLASHES OF MOLTEN 0 1 2 3 4	LARGE SPLASHES OF MOLTEN METAL 0 1 2 3 4				

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	9.00	9.50	10.00	10.50	11.00	11.50
Length	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs per carton

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

- It is cut resistant glove not cut proof, do not use them next to moving machinery.
- Do not use in cases of chemical, electrical or thermal risk.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES