Anti-static 18gg Cut Glove with Nitrile



Article No.	TS9T
Coating Material	Nitrile
Coating Color	Black
Liner	UHMWPE/Metal Wire
Liner Color	Grey
Finishing	Sandy
Cuff Style	Knit wrist
Gauge	18
Size	6,7,8,9,10,11

PERFORMANCE

- 18 gauge exclusive lining technology contributing it the thinnest cut F glove
- Over 38% lighter than a standard cut F glove
- ANSI cut level A6 certified
- EN16350 anti-static approved
- 10-finger touch screen compatible
- Perfect dexterity, flexibility, super comfort & fitting
- Super grip in both dry and wet conditions
- 360° breathability to keep your hands cool while working

APPLICATION

- Automotive industry
- Glass industry
- Paper industry
- Construction
- Electronics industry

www.fortessafety.com info@fortessafety.com Tel. +86 2157832572 Fax. +86 2157832892 Version 2021

FORTES

CERTIFICATION

EN388	ABRASION 0 1 2 3 4 TEARING 0 1 2 3 4 ISO 13997 A B C D E F	CUTTING 0 1 2 3 4 5 PUNCTURE 0 1 2 3 4	ANSI CUT	EN16350		Sanitigedi Actifrest	OEKO-TEX ® CONTRIGUCE IN TATTLES STANDARD 100 SH020 155533 TESTEX
EN407	FLAMMABILI	ГҮ		CONTA	СТ НЕАТ		
$\left(\frac{5}{5} \right)$	0 1 2 3 4 CONVECTIVE	HEAT		0 1 2 3 4 RADIAN	4 IT HEAT		
X1XXXX	0 1 2 3 4 SMALL SPLA	SHES OF MOL	TEN METAL	0 1 2 3 4 . LARGE			TEN METAL
	01234			01234	4		

For more information, please visit $\underline{\text{here}}$

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(6) X Small	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large
Palm Width	8.50	9.00	9.50	10.00	10.50	11.00
Length	22.00	23.00	24.00	25.00	26.00	27.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

- It is cut resistant glove not cut proof, do not use them next to moving machinery.
- Do not use in cases of chemical, electrical or thermal risk.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

