



Article No.	ADS35
Coating Material	Nitrile
Coating Color	Black/Wine Red
Liner	UHMWPE
Liner Color	Grey
Finishing	Flat/Sandy
Cuff style	Gauntlet
Gauge	13
Size	8,9,10,11,12

PERFORMANCE

- Waterproof & Oil repellent
- EN ISO 374-1:2016/Type B certified
- ISO 13997 TDM level C certified
- Excellent resistance to chemicals, oils, greases and acids
- Seamless knit with advanced dip technology contributing superb flexibility, dexterity and comfort
- Special wrist shape design ensuring great fitting and eliminating slippage during working
- Micro-foam with sandy finish provides super grip in particular to oily and wet working conditions
- OEKO-TEX Standard 100 certified

APPLICATION

- Mining
- Construction
- Maintenance
- Offshore petroleum
- Chemical handling
- Oil & Gas Refining

www.fortessafety.com

info@fortessafety.com







Tel. +86 2157832572

Fax. +86 2157832892

Version 2021



CERTIFICATION

EN388  4X44C	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	ANSI  A3 CUT	EN ISO 374-1:2016/Type B  AKL	EN374-5 	
	TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4				
	ISO 13997 A B C D E F					
EN407  X1XXXX	BURNING BEHAVIOUR 0 1 2 3 4	CONTACT HEAT 0 1 2 3 4				
	CONVECTIVE HEAT 0 1 2 3 4	RADIANT HEAT 0 1 2 3 4				
	SMALL SPLASHES OF MOLTEN METAL 0 1 2 3 4	LARGE SPLASHES OF MOLTEN METAL 0 1 2 3 4				

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	10.50	11.00	11.50	12.00	12.50
Length	32cm				

PACKING

Poly bag	6 pairs per poly bag with 1 consumer information sheet
Carton	60 pairs per carton

GLOVE CARE

Laundering	Rinse the gloves in running water (less than 40° C) before removing, using a neutral detergent if necessary
Storage	Store the gloves in their original packaging protected from light and humidity

RECOMMENDATION FOR USE

- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm
- Do not use in cases of electrical or thermal risk

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES