



Article No.	WL6G
Coating Material	Latex
Coating Color	Black
Liner	Acrylic /UHMWPE
Liner Color	Black
Finishing	Sandy
Cuff style	Knit wrist
Gauge	10
Size	7,8,9,10,11,12

## PERFORMANCE

- 10 gauge brushed acrylic cut resistant liner guarantees excellent cold resistance and provides extra comfort & softness compared with the standard 7 gauge one in the market
- ANSI Cut A3 and ISO13997 cut C
- Micro-foamed finish providing excellent grip, particularly to slippery object handling
- Great flexibility, dexterity and good fitting
- Sanitized® hygiene function offers increased freshness, comfort and protection from bacteria
- Multiple wash-ability and cut level remains
- Available in 3/4 coating (WL46) for more protection

## APPLICATION

- Forestry
- Construction
- Road maintenance
- Work under cold environment where cut protection required

[www.fortessafety.com](http://www.fortessafety.com)

[info@fortessafety.com](mailto:info@fortessafety.com)







Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

**FORTES**

## CERTIFICATION

<b>EN388</b>	<b>ABRASION</b>	<b>CUTTING</b>	<b>ANSI</b>		
	0 1 <b>2</b> 3 4	0 1 2 3 4 <b>5</b>			
<b>2542C</b>	<b>TEARING</b>	<b>PUNCTURE</b>	<b>ISO 13997</b>		
	0 1 2 3 <b>4</b>	0 1 <b>2</b> 3 4	A B <b>C</b> D E F	<b>CUT</b>	
<b>EN511</b>	<b>CONVECTIVE COLD</b>	<b>CONTACT COLD</b>			
	0 1 2 3 4	0 <b>1</b> 2 3 4 5			
<b>X1X</b>	<b>PERMEABILITY TO WATER</b>				
	0 1				
<b>EN407</b>	<b>FLAMMABILITY</b>	<b>CONTACT HEAT</b>			
	0 1 2 3 4	0 1 <b>2</b> 3 4			
	<b>CONVECTIVE HEAT</b>	<b>RADIANT HEAT</b>			
	0 1 2 3 4	0 1 2 3 4			
<b>X2XXXX</b>	<b>SMALL SPLASHES OF MOLTEN METAL</b>	<b>LARGE SPLASHES OF MOLTEN METAL</b>			
	0 1 2 3 4	0 1 2 3 4			

For more information, please visit [here](#)

## DIMENSIONS (+/- 0.50 cm)

Sizes Available	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	9.50	10.00	10.50	11.00	11.50	12.00
Length	23.00	24.00	25.00	26.00	27.00	28.00

## PACKING

Poly bag	12 pairs per poly bag with 1 consumer information sheet
Carton	10 poly bags of 120 pairs per carton

## GLOVE CARE

Laundering	Wash at 40°C max, using a neutral detergent
Storage	Store the gloves in their original packaging protected from heat, light and humidity

## RECOMMENDATION FOR USE

- Do not use in cases of chemical, electrical or thermal risk
- Persons sensitized to natural latex are not recommended to use this glove

[www.fortessafety.com](http://www.fortessafety.com)

[info@fortessafety.com](mailto:info@fortessafety.com)

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

**FORTES**